Hydrotherapy



Rehabilitation & Relaxation Pool

REF. 1243.00





Hydrotherapy



Rehabilitation & Relaxation Pool

REF. 1243.00

VERSIONS:

REF. 1243.00 Butterfly pool with filtering group, heater, semi automatic chlorination and pH, patient shower head.

OPTIONS:

- REF. 1243.10 Under water massage system, 6 water/air directional nozzles.
- REF. 1243.20 Air whirlpool with 20 nozzles on the ground of the pool.
- REF. 1243.30 "Kine" lance of massage 0-10 bars.
- REF. 1243.40 Automatic system of injection and self-regulation of the Chlorine and the pH. + Kit of analysis by photometer.
- REF. 1243.60 Chromotherapy option.
- REF. 1243.70 Aromatherapy option
- (incompatible without the whirlpool option) • RFE 1243.80 Protecting cover.
- REF. 8905.00 Kit of analysis for Ph and chlorine by photometer.

MAIN CHARACTERISTICS:

- Tub capacity: 1800 liters.
- Weight of the control panel: 125 kg.
- Weight of the tub without control panel: 200 kg.
- Water volume up to the handrail: 1400 liters.
- Water height up to the handrail: 50cm.Pool in white reinforced polyester.
- Frame in stainless steel, equipped with 8 adjustable feet for the leveling of the pool.
- Mixer taps Grohe with pouring spout.
- Dosing pumps injecting chlorine and pH.
- Chlorine and pH controls secured with a key.
- 2 tanks of 5L behind a trap door for the chlorine and pH.
- Patient shower head.
- Water meter.
- Skimmer with adjustment valve.
- Drain and suction part with adjustment valve.
 4 handrails in stainless steel.
- Trap doors secured by key.
- map doors secured by ke

SOUND LEVELS:

- Filtration : 47dBA
- Under water massage system : 57dBA
- Under water massage system + air injection : 61dBA
 Underwater lance of massage : 69dBA
- Air whirlpool : 73dBA

FILTRATION:

- Regeneration of the water volume (1400 liters) in 24 minutes
- Circulation pump real flow rate : 3.5m3/h
- Filter with 3 way valve (filtration, clean, rinse)
- 30kg filtering glass (improved thinness of filtration)
- 3 taps for samples supply point
 Integrated heater 3kw
- Integrated heater Skw
- Watermeter and manometer of control
- Sensitive control panel with digital thermometer, temperature graduation, clock...

CONFORMITY:

- Circular n°DGS/EA4/2010/289 dated 27th July 2010 regarding
- infection's control, especially the prevention of Legionellosis
- in spas for groups and public spaces.
- Article D1332-1 (sanitary rule for pools)
- EN 1717 (protection against pollution of drinking water in inside networks and main demands of devices against
- pollution by return)
- 73/23/CEE (directive low voltage)

UNDERWATER MASSAGE UNIT 6 NOZZLES:

- 6 directional nozzles 15cm height under the water line.
- Massage pump 20m3/h
- Control of the air/water mix since the coping of the tub.

AIR WHIRLPOOL:

- 20 air nozzles on the ground of the tub.
- Blower 1150W with integrated air heater.

«KINE» LANCE OF MASSAGE UNIT 0-10 BARS:

- 1 lance of massage.
- 1 booster rate 80L/min, pressure 1.5 to 8 bars, adjustable
- from the control panel.
- 1 pressure manometer 0 to 10 bars

AROMATHERAPY:

 1 device diffusing essential oils through the nozzles of the air whirlpool.



