

# Caleche



## Side Door Seat Bathtub

REF. 4500.10 / 4500.20 / 4501.10 / 4501.20 / 4502.10 / 4502.20

The Caleche is a low dimension bathtub which designed to maximize autonomy, comfort and The height of access located on the side of the is only 16 cm from the ground.

Coupled with the wide opening of the door, to a direct and easy access in wheelchair without to raise legs.



## Shower & Bath

### Caleche







## UNIOUE FEATURES

- Straight approach for patient from a wheelchair.
- Inner line planed for patient's convenience and security.
- Integrated stainless steel peripheral handrail.
- · Locking handle accessible from inside.
- Rounded shape.
- · Non-skid bottom.














## Side Door Seat Bathtub

## REF. 4500.10 / 4500.20 / 4501.10 / 4501.20 / 4502.10 / 4502.20







- · Bath in a sitting position.
- Step is only 16cm from the floor.
- Direct and easy access from wheelchair withtout having to raise legs.
- Low seat height and handgrips all around the bath.

#### SPECIFICATIONS:

- Maximum water volume (until overflow): 205 litres
- · Maximum height of water line :100 cm
- Weight: 85 Kg
- Maximum patient weight : 200 Kg

#### OPTIONS:

4550.00 Integrated filling spout. 4500.99 Air whirlpool system 4500.60

Chromotherapy (4 LED lamps , 7 colours) 4500.70 Aromatherapy (Air whilpool option needed)

#### VERSIONS:

#### Ref. 4500.10 (Senior version)

- · Reinforced fiberglass tub, white colour.
- Footrest and non-skid bottom.
- Intregrated stainless steel peripheral handrail.
- · Integrated soapdish.
- 4 adjustable feet (adjustable on 5cm)
- · Locking handle accessible from inside.
- Ø50mm draining by trap and Ø38mm overflow.
- Door for draining access.

#### Ref. 4500.20 (Professional version)

- Integrated and retractable hair wash basin, connected to the trap.
- · Lock.

#### Ref. 4501.10

- Specifications of 4500.10 with :
- 54 l/min "Watts" thermostatic mixer with built-in check valves and scald protection.
- · Filling valve
- Integrated filling spout.
- · Cleaning shower and its 2.3m hose.

#### Ref. 4501.20

- · Specifications of 4500.20 with:
- 54 I/min "Watts" thermostatic mixer with built-in check valves and scald protection.
- Filling valve
- Integrated filling spout.
- · Cleaning shower and its 2.3m hose.

#### Ref. 4502.10

- · Specifications of 4500.10 with:
- 48 I/min "Rada Sense" bath & shower concealed digital mixing valve offering programmable max, min & default temperatures, automatic temperature on outlet selection, duty flush and thermal disinfection with datalogging capabilities.
- · Integrated filling spout.
- · Cleaning shower and its 2.3m hose.

#### Ref. 4502.20

- · Specifications of 4500.20 with:
- 48 I/min "Rada Sense" bath & shower concealed digital mixing valve offering programmable max, min & default temperatures, automatic temperature on outlet selection, duty flush and thermal disinfection with datalogging capabilities
- · Integrated filling spout.
- · Cleaning shower and its 2.3m hose.

#### Réf. 4500.99 (air whirlpool version)

• 12 nozzles air whirlpool with integrated heater, variable speed and and drying cycle.